

























FIRECEL+ 3<sub>IN</sub>1 HAND WARMER, POWERBANK & FLASHLIGHT

Model #	48011	48012	93543	93544	
Battery Capacity	4400 mAh	4400 mAh	2500 mAh	5200 mAh	
Battery Life (Hand Warmer Function)	Up to 6 hours	Up to 6 hours	Up to 3 hours (T1 setting)	One side: Up to 12 hours Both sides: Up to 6 hours	
Battery life (Heat with Light)	- 建建筑 (4)		Up to 2.5 hours (T1 setting)	One side: Up to 11.5 hours Both sides: Up to 5.5 hours	
Hand Warmer Temperature range	103° to 114°F (40° to 45°C)	103° to 114°F (40° to 45°C)	2 Settings 1. Up to 110° 2. Up to 130°	103° to 114°F (40° to 45°C)	
IP Rating (Water/Dust Proof)		_	_	_	
Flashlight Bulb	_		4 LEDs (2) Red (2) Bright white	4 LEDs (2) Red (2) Bright white	
Flashlight Modes			1. Red ON 2. White ON 3. Red blinking 4. White blinking 5. Both S.O.S.	1. Red ON 2. White ON 3. Red blinking 4. White blinking 5. Both S.O.S.	
Power Output	_	USB Port: 5V- 1A	USB Port: 5V- 1A	USB Port: 5V- 1A	
Power Input	Mini USB Port- 5V- 900 mA	Mini USB Port - 5V 900 mA	Micro USB Port- 5V 900 mA	Mini USB Port- (smart charge) 5V-500mA to 1.8A (max)	
Auto Charge Feature	No	No	No	No	
Accessories	USB cable, protective rubber caps, and soft carry bag	USB cable, protective rubber caps, and soft carry bag	USB cable, wrist strap and soft carry bag	USB cable, wrist strap and soft carry bag	
Weight	5.22 oz./ 148 g	5.22 oz./ 148 g	4.0 oz./ 113.4g	3.52 oz./ 148 g	
Dimensions	1.76" x 3.73" x .9" (44.9mm x 94.6mm x 22.9mm)	1.76" x 3.73" x .9" (44.9mm x 94.6mm x 22.9mm)	3.5" x 2.5" x 1.0" (44.9mm x 94.6mm x 22.9mm)	2.58" x 3.49" x 0.96" (65.5mm x 88.6mm x 24.5mm)	















48023







48024



FIRECEL MEGA 3<sub>IN</sub>1 HAND WARMER.



THERMOTORCH 5 3<sub>IN</sub>1 HAND WARMER.



THERMOTORCH 10 HIGH CAPACITY POWERBANK

<b>Battery Capacity</b>	6000 mAh	
y Life (Hand Warmer)	Up to 8 hours	
life (Heat with Light)		
er Temperature range	103° to 114°F (40° to 45°C)	
ing (water/dust proof)	IP65- water resistant/dust proof	
Flashlight Bulb		
Flashlight Modes	_	
Power Output	USB Port: 5V- 2.1A	
Power Input	Mini USB Port- (smart charge) 5V-500mA to 1.8A (max)	
Auto Charge Feature	Yes	
Accessories	USB cable, carabiner with 550	
	parachord strap	
Weight	5.9 oz./ 168 g	
Dimensions	2.0" x .96" x 4.0"	
	(51.34mm x 24.41mm x 102.9mm)	

-	In the latest and the
No. of Lot	10000 mAh
	Up to 12 hours
15,000	_
	103° to 114°F (40° to 45°C)
	IP65- water resistant/dust proof
	Dual USB Ports USB Port 1: 5V-1A USB Port 2: 5V- 2.1A
	Mini USB Port- (smart charge) 5V-500mA to 1.8A (max)
	Yes
	USB cable, carabiner with 550 parachord strap
	10.1 oz./ 286 g
	2.4" x 1.4" x 4.0" (60.2mm x 33.5mm x 102.3mm)

45.3	DUUU MAH
Pann.	Up to 8 hours
	Up to 2 hours
	103° to 114°F
1	IP65- water re
	4 LEDs (2) E (2) R
	1. White ON 3. Both ON
	USB Port: 5V-
	Mini USB Port 5V-500mA to
	Yes
	USB cable, ca
	parachord stra
	6.2 oz./ 177 g
	2.0" x .96" x (52.5mm x 24

POWERBANK & FLASHLIGHT	POWERBANK & FLASHLIGHT	WITH FLASHLIGHT
93548	94552	94553
6000 mAH	5000 mAh	10000 mAh
Up to 8 hours	Up to 6 hours	Up to 10 hours
Up to 2 hours (White LEDs on)	Up to 2 hours (low setting)	Up to 6 hours (low setting)
103° to 114°F (40° to 45°C)	103° to 114°F (40° to 45°C)	103° to 114°F (40° to 45°C)
IP65- water resistant/dust proof	IP65- water resistant/dust proof	IP65- water resistant/dust proof
4 LEDs (2) Bright white (2) Red	(1) CREE® XLAMP® XP-G2, Bright White 5W LED	(1) CREE® XLAMP® XP-G2, Bright White 5W LED
1. White ON 2. Red ON 3. Both ON 4. Both S.O.S.	LOW/ 60 lumens/ 22 hours MED/ 100 lumens/ 14 hours HIGH/ 300 lumens/ 4 hours	LOW/ 60 lumens/ 48 hours MED/ 100 lumens/ 30 hours HIGH/ 300 lumens/ 8 hours
USB Port: 5V- 2.1A	USB Port: 5V- 2.1A	Dual USB Ports USB Port 1: 5V-1A USB Port 2: 5V- 2.1A
Mini USB Port- (smart charge) 5V-500mA to 1.8A (max)	Mini USB Port- (smart charge) 5V-500mA to 1.8A (max)	Mini USB Port- (smart charge) 5V-500mA to 1.8A (max)
Yes	Yes	Yes
USB cable, carabiner with 550 parachord strap	USB cable, rugged canvas holster	USB cable, rugged canvas holster
6.2 oz./ 177 g	12.45 oz./ 353g	17 oz/ 486g
2.0" x .96" x 4.6"	6.5" x 2" x 2"	8.25" x 2" x2"
(52.5mm x 24.42mm x 117.7mm)	(165mm x 52.5mm x 52.5mm)	(208.3mm x 52.5mm x 52.5mm)



